

Easimark III Resin Enhanced Wax

Low Print Energy Prolongs Printhead Life



Food/Beverage



Health/Beauty



Logistics



Retail



The printhead cleaner built in your ribbon.

Benefits

- Outstanding print performance on coated stocks
- Performs well at lower darkness settings for longer printhead life
- Resin-enhanced provides good durability
- Designed for general purpose labeling
- Specially formulated backcoat protects the printhead
- Clean Start® built-in printhead cleaner maintains print quality

Recommended Stocks

Paper

- Vellum
- Matte Coated
- Semi-Gloss
- Gloss
- Floodcoats

Synthetics

- PP / Polypropylene
- PE / Polyethylene

Applications

- Compliance labeling
- Component identification
- Hang tags
- Ingredient lists
- Prepared foods
- Prime label
- Product identification
- Shipping
- Warehousing
- Work in Process (WIP)

Key Product Range

STANDARD WAX	ENHANCED WAX	WAX RESIN	RESIN
GoMark 100	Cleanmark Easimark III Go-Label Color	FastMark	Ultraplate II PrintGuard

Technical Specifications

Color Code Tab Purple
 Film Thickness 4.5 Microns
 Total Ribbon Thickness 7.5 Microns
 Transmission Density 1.45 MacBeth Scale
 Ink Melting Point 62°C / 144°F

Imaging Characteristics

Printer Flathead
 Max Print Speed 10 IPS (254 mm/s)
 Image Darkness 1.8 RD (densitometer)

Compliance

- REACH – SVHC Free
- RoHS/WEEE
- California Proposition 65
- Additional Regulatory Requirements Upon Request

Sample SKUs

Part # CES11011 – 110 mm x 50 m – CSI
 Part # CES11012 – 110 mm x 50 m – CSO

Storage Conditions

12 months recommended
 20-85% Relative Humidity Rate, 23-104°F (-5-40°C)

Performance Ratings

