

Go-Mark 100 Standard Wax

Efficient Wax Thermal Transfer Ribbon



Food/Beverage



Health/Beauty



Logistics



Retail



The printhead cleaner *built in* your ribbon.

Benefits

- Handles general purpose applications with ease
- Highly compatible - no printer adjustments
- Remarkable blackness in print quality
- Good stock latitude from rough to smooth coated papers
- Excellent print quality on flood coated labels
- Specially formulated backcoat protects the printhead
- Clean Start® built-in printhead cleaner maintains print quality

Recommended Stocks

Paper

- Vellum
- Matte Coated
- Semi-Gloss
- Gloss
- Floodcoats

Applications

- Compliance labeling
- Component identification
- Hang tags
- Ingredient lists
- Prepared foods
- Prime label
- Product identification
- Shipping
- Warehousing
- Work in Process (WIP)

Key Product Range

STANDARD WAX	ENHANCED WAX	WAX RESIN	RESIN
GoMark 100	Cleanmark Easimark III Go-Label Color	FastMark	Ultraplate II PrintGuard

Technical Specifications

Color Code Tab Red
 Film Thickness 4.5 Microns
 Total Ribbon Thickness 8.1 Microns
 Transmission Density >4.0 MacBeth Scale
 Ink Melting Point 67°C / 152°F

Imaging Characteristics

Printer Flathead
 Max Print Speed 10 IPS (254 mm/s)
 Image Darkness 1.9 RD (densitometer)

Compliance

- REACH – SVHC Free
- RoHS/WEEE
- California Proposition 65
- Additional Regulatory Requirements Upon Request

Sample SKUs

Part # CES11033 - 110 mm x 50 m - CSI
 Part # CES11032 - 110 mm x 50 m - CSO

Storage Conditions

12 months recommended
 20-85% Relative Humidity Rate, 23-104°F (-5-40°C)

Performance Ratings

